



VIN-FP-200/007

climalife®

R-408A

(ZEOTROPIC MIXTURE)

GUARANTEED COMMERCIAL SPECIFICATIONS

STANDARD SPECIFICATIONS	LIMIT VALUE
Composition:	
- R-125	7 % (± 2 %)
- R-143a	46 % (± 1 %)
- R-22	47 % (± 2 %)
Guaranteed purity	≥ 99.5 % weight
Water content	≤ 20 ppm weight
Acidity (HCl)	≤ 5 ppm weight
Non-condensable content (gas phase)	≤ 1.5 % volume
High boiling residues	≤ 0.01 % volume

MAIN APPLICATIONS

R-408A is a HCFC type "near-zeotropic" transition mixture, of usage regulated over time (Montreal Protocol), designed for current R-502 (CFC) uses in commercial and industrial cooling domains.

It is preferably used for conversions in central refrigerating plants for superstores, refrigerated warehouses, food deep-freezing facilities, and equipment for frozen food conservation.

OILS

Use an alkylbenzene (AB), mineral (MN) or even polyol ester (POE) oil in agreement with the compressor manufacturer.

Check with **Climalife** regarding the viscosity of the oil selected for your application, and the miscibility with the fluid under consideration.

PRECAUTIONS OF USE

Refer to the Safety Data Sheet*.

REGULATION

Using **R-408A** is governed by European regulation n° 2037/2000 of June 29, 2000:

- using **R-408A** is completely prohibited in new setup as of 12.31.2003
- using virgin **R-408A** is prohibited for maintenance and service as of 01.01.2010
- using **R-408A**, even recycled, is completely prohibited as of 01.01.2015.

In Europe, **R-408A** recovery is mandatory as per regulation n° 842/2006.

(Refer to regulations enforced in each country)

* Find the Safety Data Sheet (SDS) directly on our website www.climalife.dehon.com



R-408 A

climalife®

R-408A PHYSICO-CHEMICAL PROPERTIES

Molar mass	g/mol	87
Melting point	°C	N/A
Boiling point (under 1.013 bar)	°C	-44,58
Temperature drift under 1.013 bar	K	0.46
Saturated fluid density at 25°C	kg/m ³	1059
Saturated vapour density at boiling point	kg/m ³	4.835
Vapour pressure at: 25°C 50°C	bar	11,67 21,47
Critical temperature	°C	83.14
Critical pressure	bar	42,95
Critical density	kg/m ³	485
Latent heat of vaporisation at boiling point	kJ/kg	225,78
Thermal conductivity at 25°C Liquid	W/(m.K)	0.075
Vapour under 1.013 bar		0.013
Surface tension at 25°C	10 ⁻³ N/m	6.04
Viscosity at 25°C Liquid	10 ⁻³ Pa-s	0.138
Vapour under 1.013 bar		0.012
Specific heat at 25°C Liquid	kJ/(kg.K)	1.448
Vapour under 1.013 bar	kJ/(kg.K)	0.803
Cp/Cv ratio at 25°C under 1.013 bar		1.148
Flammability in air		Non-flammable
Flashing point		none
NF- EN 378 classification		A1
ASHRAE		A1
Potential effect on ozone	(R-11 = 1)	0
GWP 4th Assessment /5th Assessment	(CO ₂ = 1)	3152/3257

Please contact your distributor or **Climalife** sales department for more information. Also, if the refrigerated system you want to install does not appear to you as a typical case, we are at your service to provide opinions and advices.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.

For more information, please visit our website:
http://www.climalife.dehon.com/contact_us